



CCW-702 WB

High-Tack, Water-Based Contact Adhesive

DESCRIPTION

CCW-702 WB is a high-tack, water-based contact adhesive for promoting adhesion of CCW self adhering sheet membranes in air/vapor barrier, window flashing, thru-wall flashing, foundation waterproofing and steep slope roofing underlayment applications. Product works well on rough and porous substrates such as DensGlass Gold®, similar exterior gypsum sheathing products, concrete masonry unit (CMU) construction, oriented strand board (OSB) sheathing and concrete.

APPLICATION

Apply by roller, brush or spray. Coverage varies by substrate as follows.

Substrate	Approximate Coverage
DensGlass Gold	200 sq ft per gallon
CMU	200 sq ft per gallon
OSB	300 sq ft per gallon
Concrete	350 sq ft per gallon

For spray application, several types of sprayers may be used, including Airless, Air-Assist and Hudson. Apply product to surface in even coat without puddles or drips. Allow to dry until there is no transfer when touched with finger. Apply to surface the same day of application of self adhering membrane.

PACKAGING

5 Gallon pails

Do not store product in direct sunlight or at temperatures above 110°F or below 35°F. Improper storage may lead to product deterioration.

CAUTION

Avoid contact with eyes and skin. In the event of contact, wash off immediately. Refer to MSDS for other important warnings and product safety information.

TECHNICAL DATA

PROPERTY	METHOD	RESULTS
Color	—	Color
Weight per Gallon	—	8.5 lb/gal
% Solids	—	46%
VOC	—	57 g/l
Drying Time, Applied to Dens-Glass Gold at ambient conditions 75°F/50% RH	—	Dry to the touch 30-45 minutes
Peel Adhesion of CCW Self Adhering Sheet Membrane (CCW-705 Standard)	ASTM D903	DensGlass Gold(new) = 9.45 lb/in OSB = 9.15 lb/in Concrete = 9.65 lb/in CMU = 8.9 lb/in
Minimum Application Temp	—	40°F
Storage Temp	—	35°F-110°F

LIMITED WARRANTY

Carlisle Coatings & Waterproofing, Incorporated (Carlisle) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any Carlisle materials prove to contain manufacturing defects that substantially effect their performance, Carlisle will, at its option, replace the materials or refund its purchase price.

This limited warranty is the only warranty extended by Carlisle with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. Carlisle specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever.

The dollar value of Carlisle's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the Carlisle material in question.

