



WATERPROOFING

MiraDRAIN® 9800

Description

CCW MiraDRAIN 9800 is a high-performance, high-strength drainage composite consisting of a three-dimensional, high-impact polystyrene core, and a superior, heavy-weight nonwoven filter fabric. The filter fabric is bonded to the individual dimples of the molded polystyrene core to minimize fabric intrusion into the flow channels caused by backfill pressure. The fabric provides unmatched filtration, preventing small particles of soil from clogging the drainage channel while allowing subgrade moisture to pass freely.

MiraDRAIN 9800 is designed for use in high-flow, high-compressive-strength, horizontal and vertical drainage applications where maximum filtration is required for subsurface drainage.

The flat side of MiraDRAIN 9800 fits directly against wall or deck surfaces making it ideal for planter, green roof and foundation wall applications. MiraDRAIN 9800 also serves as a protection course over CCW Waterproofing Membranes.

Features and Benefits

- Relieves hydrostatic pressure buildup against subterranean surfaces.
- Consistent, multi-directional core configuration provides a uniform flow path for water to escape
- High-flow drainage capacity - up to three times the flow capacity of aggregate or sand
- No-clogging drainage performance
- High-compressive-strength system withstands installation and in-situ earth stresses
- Enhances waterproofing system by channeling water away and providing a secondary water retention layer
- Cost-saving, lightweight, easy-to-install panels eliminate the need for aggregate

Installation

MiraDRAIN prefabricated drainage panels may be installed in a variety of construction applications. They may be installed against waterproofed retaining and foundation walls and planters. MiraDRAIN can be cut with a utility knife or scissors. The panels can terminate at the top of the footing and are flexible enough to form right angles to cover the top of the footing. MiraDRAIN eliminates the need for a protection course over waterproofing systems. Native soils can be used over MiraDRAIN. (Contact your local CCW representative for specific guidelines).

For standard installation details, follow the MiraDRAIN detail drawings. For non-standard installation instructions contact your local Carlisle Coatings & Waterproofing representative.

Foundation Walls/Vertical Applications

The MiraDRAIN panel can be installed in rows or columns with the fabric side toward the soil. Each method has its advantages depending on the criteria of the project as to which method is best.

When installing the MiraDRAIN in rows:

- Place the longitudinal edge of the core against the wall so that it is flush with the wall footing.
- Attach subsequent panels in shingle fashion with fabric overlap at bottom, placing the longitudinal edge of the upper panel over the flanged longitudinal edge of the lower panel and lap fabric from upper panel over lower panel.

When installing the MiraDRAIN in columns:

- Start at the low point of the wall and attach the panel to the wall.
- Adjacent panels should be joined together with the lateral edge of the connecting panel placed over the flanged edge of the previous panel.

The fabric from the adjacent panels should overlap the preceding panel. The fabric can be adhered with CCW CAV-GRIP, CCW Contact Adhesive, CCW-704 Mastic, CCW LM-800XL or duct tape. The top or terminal edge of the MiraDRAIN should be sealed by wrapping the extra filter fabric around to the back side of the panel, and if there is insufficient fabric, the core shall be cut out from the fabric by a depth of 3 dimples to provide excess fabric for wrapping behind the core. This will prevent soil or other foreign construction materials from intruding into or behind the panels. A "set back" or "ledge" condition may be encountered on some construction applications. Where this condition exists, MiraDRAIN panels should be installed beginning at the bottom of the wall and ending at the ledge. Subsequent courses of MiraDRAIN should be installed flat against the upper wall portion and placed so that 4" to 6" (10-15 cm) extend down and over the lower edge. The overlapping MiraDRAIN sections will be pushed flush against the wall during backfilling.

Attachment Method – CCW Waterproofing Membranes

The MiraDRAIN should be attached with CCW CAV-GRIP, CCW Contact Adhesive, CCW Seam Tape or SecurTAPE™. Apply CCW CAV-GRIP or CCW Contact Adhesive over entire surface of waterproofing membrane and mate the two surfaces together. The MiraDRAIN will be permanently secured upon completion of backfill. Backfill should be placed as soon as possible. Backfill to at least 6" (15 cm) above the top edge of the MiraDRAIN.

WATERPROOFING

MiraDRAIN 9800

Attachment Method – CCW MiraCLAY Waterproofing Membrane

The MiraDRAIN should be attached over the CCW MiraCLAY membrane using fasteners compatible with substrate and 1" washers.

Underslab/Horizontal Applications

Floor Slabs and Concrete-Lined Channels: Proper preparation of the subgrade will require grading to a 2% minimum slope. The area of installation should be clear of rubble, rock, large soil clods, etc. Place CCW MiraDRAIN with the fabric side toward the soil. The flange of the second and subsequent panels should be placed over the back side of the preceding dimpled core and butted as close as possible to the preceding panel. The panel joints, longitudinal and transverse on the MiraDRAIN core, should be sealed with a strip of CCW-705, CCW-701 or duct tape. This will aid in preventing concrete or soil from intruding into the MiraDRAIN core during subsequent construction phases. Construction traffic should be minimized over the installed MiraDRAIN. Sand and/or concrete may be poured directly over the MiraDRAIN core.

Planters: Place the MiraDRAIN in the planter so that the fabric on the vertical and horizontal surfaces faces the soil. Utilize the installation procedures and attachment method appropriate for the type of substrate. Overlap the fabric of the vertical panel onto the horizontal panel at the transition point. If cutting of the panels is required, exposed cuts must be covered with supplemental pieces of filter fabric to prevent soil intrusion. A minimum overlap of 6" (15 cm) will be required to cover cut sections.

Plaza Decks: Place fabric side up over a properly waterproofed substrate. The panels should be placed so that water runs with the overlap not against it. Secure MiraDRAIN to the substrate with ballast or CCW CAV-GRIP, CCW Contact Adhesive or SecurTAPE to hold it in place. The first panels should be placed with the flanged edge uphill. Cut the fabric along the flange edge and strip off this fabric exposing the edge of the core and the flange. Place the dimpled edge over the preceding flanged edge to join the next panel. Secure the remaining fabric flap with CCW CAV-GRIP, CCW Contact Adhesive, CCW-704 Mastic, CCW LM800-XL, Aluma-Grip 701 or duct tape. Terminal edges that have been cut will require a supplemental piece of filter fabric to seal the panel from soil intrusion and if there is insufficient fabric, the core shall be cut out from the fabric by a depth of 3 dimples to provide excess fabric for wrapping behind the core.

Drainage Collector/Discharge System

Collector Pipe: Place collector pipe as required in design details. For installations where a collector pipe is specified, encapsulate the collector pipe in a gravel bed with a supplemental section of filter fabric as a separator/filter.

Packaging

4' x 50' (1.22 m x 15.24 m) rolls

MiraDRAIN 9800 is made in the USA and is sold through a highly qualified sales representative network.

Limitations

- Limit ultraviolet exposure by backfilling with 30 days of installation. Any panels damaged during installation should be replaced by the installer.
- MiraDRAIN is resistant to chemicals in normal soil environments. However, some reagents may affect its performance. CCW representatives should be consulted concerning the suitability of MiraDRAIN in unusual soil environments.

Typical Properties

Property	Method	Unit	Typical Value
CORE			
Thickness	ASTM D1777	in (mm)	0.40 (10.16)
Compressive Strength	ASTM D1621 (mod)	psf (kPa)	18,000 (862)
Maximum Flow Rate ¹	ASTM D4716	gpm/ft (l/min/m)	17.5 (219)
Installed Vertically ²	ASTM D4716	gpm/ft (l/min/m)	15.5 (193)
Installed Horizontally ³	ASTM D4716	gpm/ft (l/min/m)	3.0 (38)
FABRIC (180N)			
Apparent Opening Size	ASTM D4751	US Std Sieve (mm)	80 (0.18)
Water Flow Rate	ASTM D4491	gpm/ft ² (l/min/m)	95 (3870)
Grab Tensile Strength	ASTM D4632	lbs (kN)	205 (912)
Grab Longation	ASTM D4632	%	50
CBR Puncture Strength	ASTM D6241	lbs (kN)	500 (2224)
SYSTEM			
Performance Index	*		31,325

All flow rates were tested at 3600 psf.

¹In plane flow rate @ gradient of 1.0

²Installed flow rate with soil overburden @ vertical gradient of 1.0

³Installed flow rate with concrete overburden @ horizontal gradient of 0.05 *Drainage Performance Index is a function of ASTM D 4833, D 4632 and D 1621

Limited Warranty

Carlisle Coatings & Waterproofing Incorporated (Carlisle) warrants this product to be free of defects in workmanship and materials only at the time of shipment from our factory. If any Carlisle materials prove to contain manufacturing defects that substantially affect their performance, Carlisle will, at its option, replace the materials or refund its purchase price. This limited warranty is the only warranty extended by Carlisle with respect to its materials. There are no other warranties, including the implied warranties of merchantability and fitness for a particular purpose. Carlisle specifically disclaims liability for any incidental, consequential, or other damages, including but not limited to, loss of profits or damages to a structure or its contents, arising under any theory of law whatsoever. The dollar value of Carlisle's liability and buyer's remedy under this limited warranty shall not exceed the purchase price of the Carlisle material in question.